

SECURITY STARTS WITH
PHYSICAL DEFENSE.

HELICAL BARBED TAPE



Minimum Security Applications

- Reliable Perimeter Protection for Low-Risk Sites
- Designed for perimeter security in non-critical or low-threat environments
- Ideal for residential zones, warehouses, and industrial yards
- Features long-barb, wire-reinforced coils formed without clips for cleaner deployment
- Available in galvanized or stainless steel options for enhanced durability
- Compatible with walls, chain link fences, or standalone posts

Typical Uses: Warehouses • Construction sites • Parking lots • Storage facilities • Solar farms • Low-security residential or commercial perimeters



Walstar Code #	NSN	DESCRIPTION	DIA. (in)	COIL LOOPS	STRIP MATERIAL	CORE WIRE	CLIPS	LOOP SPACING (in)	YIELD (ft)	ASTM F 1910
IMPORT STOCK ITEM										
RAZRIBGGIMP	5660-01-495-6123	GG Helical 18", 33L, 50'	18	33	Galvanized	Galvanized	0	18	50	—
RAZRIBSGIMP	5660-01-457-9757	SG Helical 18", 33L, 50'	18	33	Stainless Steel	Galvanized	0	18	50	#2
USA MADE STOCK ITEM										
RAZRIBSGI8	5660-01-457-9757	SG Helical 18", 33L, 50'	18	33	Stainless Steel	Galvanized	0	18	50	#2
RAZRIBSG24	5660-01-457-9842	SG Helical 24", 33L, 50'	18	33	Stainless Steel	Galvanized	0	18	50	#6

NOTE: **Strip Material:**
Galvanized: Galv. 0.80 oz/sqft .024" thk
Stainless Steel: SS430 .025" thk

Core Wire Material:
Galvanized: .098" (12.5 Ga) Galv. 0.80 oz/sqft 180-195 Ksi
Stainless Steel: .098" (12.5 Ga) SS304 180-195 Ksi

Packaging:
All packages include 5 coils per box.

BARB OPTION:



Long Barb

SECURITY STARTS WITH
PHYSICAL DEFENSE.

BARBED TAPE CONCERTINA



Medium to Maximum Security Applications

- Suitable for medium to maximum security perimeter protection
- Wire-reinforced concertina coils with long-barb profile for strong deterrence
- Tightly clipped coils ensure minimal spacing for intrusion resistance
- Available in galvanized or stainless steel for durability in all climates
- Compatible with fence tops, walls, and standalone systems

Typical Use Cases: Detention centers • Confinement facilities • Utility substations
• Solar farms • Airport perimeters • Industrial yards



Walstar Code #	NSN	DESCRIPTION	DIA. (in)	COIL LOOPS	STRIP MATERIAL	CORE WIRE	CLIPS	LOOP SPACING (in)	YIELD (ft)	ASTM F 1910
USA MADE MADE TO ORDER										
RAZTRIBSGM18	5660-01-457-9847	SG 18" Maze 31L 15'	18	31	Stainless Steel	Galvanized	3	16	15	#8
RAZTRIBSGM24	5660-01-457-9850	SG 24" Maze 31L 20'	24	31	Stainless Steel	Galvanized	3	16	20	#10
RAZTRIBSGM2430	—	SG 24"/30" Maze 31L 20'	24/30	31/31	Stainless Steel	Galvanized	3	16/16	20	#21
RAZTRIBSSM24	5660-01-457-9852	SS 24" Maze 31L 20'	24	31	Stainless Steel	Stainless Steel	3	16	20	#11
RAZTRIBSSM30	—	SS 30" Maze 31L 20'	30	31	Stainless Steel	Stainless Steel	3	16	20	—
RAZTRIBSSSM30	5660-01-495-9534	SS 30" Super Maze 51L 25'	30	51	Stainless Steel	Stainless Steel	5	12	25	#15

NOTE:

Strip Material:

Galvanized: Galv. 0.80 oz/sqft .024" thk
Stainless Steel: SS430 .025" thk

Core Wire Material:

Galvanized: .098" (12.5 Ga) Galv. 0.80 oz/sqft 180-195 Ksi
Stainless Steel: .098" (12.5 Ga) SS304 180-195 Ksi

Packaging:

All packages include 5 coils per box.

BARB OPTION:



Long Barb

